

Canister HEPA Vacuum

- the reliable choice for demanding applications

The durable GD 930 is designed for solid performance in challenging environments such as mold, lead or asbestos remediation. This model meets requirements for the U.S. EPA's Lead Renovation, Repair and Painting Program when equipped with a carpet beater bar floor nozzle.

Features and Benefits

Superior Performance and Easy to Maintain

- Preserve indoor air quality with multi-stage filtration system featuring a paper bag, foam filter and certified upstream HEPA filter
- Withstand heavy duty use with sturdy stainless steel container
- Easy to maneuver with large wheels, casters and convenient carrying handle
- Quiet operation with low decibel level

Standard Accessories Include:

6 ft. hose with bent-end wand, telescopic aluminum wand, combination floor nozzle, crevice nozzle, combination round dust brush/upholstery nozzle and paper dust bag.

Carpet beater bar tool comes in turbo nozzle (powered by working air) and power nozzle (powered by electricity) versions. Nozzles sold separately.


Technical Specifications

Description	Unit	GD 930
Collection Type	-	Dry
Type of Power	-	1-Phase
Voltage @ 60 Hz	V	110-120
Power @ 60 Hz, max.	HP (W)	1.34 (1000)
Waterlift, max.	in. (mm) H ₂ O	92 (2345)
Airflow, max.	CFM (L/min)	74 (100)
Current, max.	amps	8.7
Paper Bag Capacity	gallons (L)	4 (15)
HEPA Filter Area, upstream	ft ² (m ²)	13.13 (1.2)
HEPA Filter Efficiency	-	99.97% @ 0.3 μ
Hose Orifice Diameter	mm	32
Dimensions (L x W x H)	in. (mm)	17.5 x 15.0 x 13.0 (445 x 381 x 330)
Weight	lb. (kg)	16.5 (8)
Cord Length	ft. (m)	32 (10)
Protection Class	-	IP20
Sound Pressure Level @ 6' 6"	dB(A)	53

Specifications and details are subject to change without prior notice.



Upstream HEPA filter



High efficiency filter bags